

Stationary shelving set norm 5 with louvred shelfwe make work flow

P/N: N5BR19004001600 | RG-RS/N20/12 600kg 1600/400

Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Modular dimension: 150 mm

Max. section load 600

Carbon footprint (TM65 Basic Report) 58 kgCO□e

Weight: 34 kg

Width: 1875 mm

Depth: 400 mm

Height: 1600 mm

Modular shelving system made of plain anodised aluminium in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140 $^{\circ}$ F (-40 to +60 $^{\circ}$ C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of special 1.0×1.0 " (25 × 25 mm) square tubes, connected and stabilised by press-fitted 1.6×0 . 28" (40 × 7 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded shelf lugs at distances of 5.9" (150 mm) for easy attaching of shelves.

Time and date of the request: 18.11.2025, 14:03:37

All information / dimensions are approximate, technical changes reserved. © Hupfer