


P/N: N5DR42006001400 | TTW/E 3/30 EN/GN 115-L

Technical data



Similar to illustration, technical modifications reserved. Without decoration.

Cleaning classification:	Suitable for washing devices
Maximum dimension:	530 x 370/325/375 mm
Capacity:	30 trays EN, GN or Veska standard
Modular dimension:	115 mm
Insertion type:	Lengthwise
Max. bay load	150
Max. section load	600
Carbon footprint (TM65 Basic Report)	910 kgCO⊡e
-1	
Payload:	150 kg
•	150 kg 2 fixed castors, 2 swivel castors with lock Ø 160
Payload:	2 fixed castors, 2 swivel castors
Payload: Castors:	2 fixed castors, 2 swivel castors with lock Ø 160
Payload: Castors: Main construction:	2 fixed castors, 2 swivel castors with lock Ø 160 Closed, single-walled, three-part
Payload: Castors: Main construction: Design:	2 fixed castors, 2 swivel castors with lock Ø 160 Closed, single-walled, three-part 3 compartments, 3 x 10 shelf pairs
Payload: Castors: Main construction: Design: Weight:	2 fixed castors, 2 swivel castors with lock Ø 160 Closed, single-walled, three-part 3 compartments, 3 x 10 shelf pairs 90 kg

Tray transport trolley for storing meal components on Euronorm, Gastronorm or H+ trays.

Trolley made entirely of high-quality stainless steel, self-supporting design. Single-walled tray transport trolley closed on all sides. Double-walled double-wing doors that can be opened by 270° using a continuous vertical handle bar, automatic closing mechanism, single-handed operation, lock via transport latch with sealing option. Rear wall with triple rolled bead for sound insulation. Interior split in three through removable support ledge frames with 1.6/1.6" (40/40 mm) L-shaped angles, adjustable for 10 EN, GN or H+ standard trays each per compartment for lengthwise insertion. Four continuous vertical push bars (2 on each side), for easy manoeuvring. Dimensionally stable chassis design, suitable for delivery transport. In addition, the use in automatic trolley transport is possible. Bumper protective feature provided by two robust, continuous bumper strips at the chassis. Trolley runs on 2 swivel casters with total lock, 2 fixed casters, fastened by means of screw-

Time and date of the request: All information / dimensions are approximate, technical changes reserved. © Hupfer 11.09.2025, 20:45:06

Hupfer · Dieselstrasse 20, 48653 COESFELD · Postfach 1463, 48634 COESFELD · Tel.: +49 2541 805-0 · Fax: +49 2541 805-111 info@hupfer.de · www.hupfer.com



P/N: N5DR42006001400 | TTW/E 3/30 EN/GN 115-L

on plates and four screws.

The Hupfer tray transport trolley TTW / E 3/30 EN/GN-115 L features removable tray racks, providing great variability in combination with optimal cleaning results. The use of L-shaped shelf rails allows both conventional trays in the Euro norm, gastronorm and Veska norm formats as well as system trays to be used. The very low space requirements in comparison to other products, along with four vertical push bars, ensure effortless handling for persons of any size.

All information / dimensions are approximate, technical changes reserved. $\ensuremath{\mathbb{C}}$ Hupfer

Hupfer · Dieselstrasse 20, 48653 COESFELD · Postfach 1463, 48634 COESFELD · Tel.: +49 2541 805-0 · Fax: +49 2541 805-111 info@hupfer.de · www.hupfer.com