

# Stationary shelving set norm 5 with solid shelf

P/N: N5GS22003002000 | TTW/E 3/24 EN/GN 115-L

**HUPFER**  
we make work flow

## Technical data



*Similar to illustration, technical modifications reserved. Without decoration.*

<b>Cleaning classification:</b>	Suitable for washing devices
<b>Maximum dimension:</b>	530x370/325/375 mm
<b>Capacity:</b>	24 trays EN, GN or Veska standard
<b>Modular dimension:</b>	115 mm
<b>Insertion type:</b>	Lengthwise
<b>Max. bay load</b>	150
<b>Max. section load</b>	600
<b>Carbon footprint (TM65 Midlevel Report)</b>	355 kgCO <sub>2</sub> e
<b>TM65 Midlevel Report</b>	<a href="#">Link to the certificate</a>
<b>Payload:</b>	120 kg
<b>Castors:</b>	2 fixed castors, 2 swivel castors with lock Ø 160
<b>Main construction:</b>	Closed, single-walled, three-part
<b>Design:</b>	3 compartments, 3 x 8 shelf pairs
<b>Weight:</b>	38 kg
<b>Width:</b>	2175 mm
<b>Depth:</b>	300 mm
<b>Height:</b>	2000 mm

Tray transport trolley for storing meal components on Euronorm, Gastronorm or H+ trays.

Trolley made entirely of high-quality stainless steel, self-supporting design. Single-walled tray transport trolley closed on all sides. Double-walled double-wing doors that can be opened by 270° using a continuous vertical handle bar, automatic closing mechanism, single-handed operation, lock via transport latch with sealing option. Rear wall with triple rolled bead for sound insulation. Interior split in three through removable support ledge frames with 1.6/1.6" (40/40 mm) L-shaped angles, adjustable for 8 EN, GN or H+ standard trays each per compartment for lengthwise insertion. Four continuous vertical push bars (2 on each side), for easy manoeuvring. Dimensionally stable chassis design, suitable for delivery transport. In addition, the use in automatic trolley transport is possible. Bumper protective feature provided by two robust, continuous bumper

Time and date of the request: 10.05.2026, 01:36:30 *All information / dimensions are approximate, technical changes reserved. © Hupfer*

## Stationary shelving set norm 5 with solid shelf

**HUPFER**  
we make work flow

P/N: N5GS22003002000 | TTW/E 3/24 EN/GN 115-L

strips at the chassis. Trolley runs on 2 swivel casters with total lock, 2 fixed casters, fastened by means of screw-on plates and four screws.

The Hupfer tray transport trolley TTW / E 3/24 EN/GN 115-L features removable tray racks, providing great variability in combination with optimal cleaning results. The use of L-shaped shelf rails allows both conventional trays in the Euro norm, gastronorm and Veska norm formats as well as system trays to be used. The very low space requirements in comparison to other products, along with four vertical push bars, ensure effortless handling for persons of any size.

Time and date of the request: 10.05.2026, 01:36:30 *All information / dimensions are approximate, technical changes reserved. © Hupfer*