Technical data

Similar to illustration, technical modifications reserved. Without decoration.

Maximum dimension:	1,600 × 700 mm
Base dimensions:	1,450 × 600 mm
Rectangular tubing base:	40 × 40 mm
Height adjustment range (stroke):	300 mm
Worktop thickness:	1.5 mm
Bevelled worktop edges:	50 mm
Payload:	245 kg/540 lbs
Main construction:	Open
Capacity:	240 W
Supply voltage:	230 V AC
Nominal current:	1.04 A
Protection class:	IPX4
Frequency:	50 Hz
Weight:	50 kg
Width:	2375 mm
Depth:	500 mm
Height:	1200 mm

Packing table made of high-quality stainless steel in hygienic design, with hydraulic height adjustment system for ergonomic adaptation to different body sizes.

Robust design made of square tubes, worktop folded on all sides. Underside of tabletop reinforced by profiles and fitted with a stainless steel pan, housing and protecting the hydraulic system for height adjustment. Lift cylinders with adjustment feet ensure compensation of floor unevennesses. Hydraulic, infinitely variable height adjustment system integrated into feet, for adaptation to different user body heights. Chassis with four feet for worktops up to a length of 87'' (2200 mm), with six feet for greater lengths. Struts in base on three sides for enhanced rigidity and optimum attaching of shelves.

The Hupfer height-adjustable packing table PT-EH 1600/700/850-1150 allows infinite height adjustment,

Time and date of the request:
13.09.2025, 18:08:02

All information / dimensions are approximate, technical changes reserved. © Hupfer

Hupfer · Dieselstrasse 20, 48653 COESFELD · Postfach 1463, 48634 COESFELD · Tel.: +49 2541 805-0 · Fax: +49 2541 805-111
info@hupfer.de · www.hupfer.com

ensuring it provides a wide range of individual options for use, as well as options for adapting it to diverse circumstances. The digital display ensures an exact and easy-to-read indication of the set working height.

Time and date of the request: *All information / dimensions are approximate, technical changes reserved. © Hupfer*
13.09.2025, 18:08:02