

# Stationary shelving set norm 5 with solid shelf

P/N: N5GS43003001400 | RG-RS/N20/12 1200kg 1800/400

**HUPFER**  
we make work flow

## Technical data



<b>Modular dimension:</b>	150 mm
<b>Max. section load</b>	1200
<b>Carbon footprint (TM65 Basic Report)</b>	645 kgCO <sub>2</sub> e
<b>Weight:</b>	64 kg
<b>Width:</b>	4225 mm
<b>Depth:</b>	300 mm
<b>Height:</b>	1400 mm

*Similar to illustration, technical modifications reserved. Without decoration.*

Modular shelving system made of plain anodised aluminium in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of special 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 1.6 × 0.28" (40 × 7 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded shelf lugs at distances of 5.9" (150 mm) for easy attaching of shelves.

Time and date of the request:  
13.09.2025, 19:29:11

*All information / dimensions are approximate, technical changes reserved. © Hupfer*