Stationary shelving set norm 5 with solid shelf



1600 mm

P/N: N5GS8004001600 | GSW 10x6/3

Technical data



Similar to illustration, technical modifications reserved. Without decoration.

Modular dimension:150 mmCarbon footprint (TM65 Basic Report)177 kgCOllePayload:120 kgWeight:19 kgWidth:800 mmDepth:400 mm

Serving trolley in closed version with deep-drawn shelves.

Trolley in robust, self-supporting and hygienic design, made of high-quality stainless steel. \emptyset 1.0" (25 mm) round tube frame with 3 welded, 31.5 × 19.7" (1000 × 600 mm) deep-drawn shelves with 0.4" (10 mm) high profile edge, lined with sound insulation on the underside, hygienically folded by 1.4" (35 mm) and rebated inwards, designed for easy cleaning. Push bars integrated on both sides into tube frame ensure good manoeuvrability. Trolley with stainless steel panels on three sides and double-wing doors with grip opening and magnetic catch. 4 polypropylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks, \emptyset 4.9" (125 mm), chrome-galvanised housing, plastic caster wheel with roller bearing, failsafe running tread identical to pneumatic casters, with pin fastening.

Height:

The Hupfer serving trolley GSW $10 \times 6 / 3$ is a welded model delivered ready for use, and also has full stainless steel panelling, including doors. The smooth and cavity-free raised edges makes this model easy to clean, and prevents dirt from accumulating in the corners. The air-free and puncture-proof tyres ensure running noises are kept to a minimum, and make it especially suitable for uneven flooring.

Time and date of the request: 24.11.2025, 17:37:48

All information / dimensions are approximate, technical changes reserved. © Hupfer