

Gastronorm trolley for 36×GN 1/1

Технические характеристики изделия 0112535 | RWG 1/36 GN 75-B-U



Технические характеристики

Размер ячейки: 75 mm

Тип шин: Crosswise insertion

739 мм

Полезная нагрузка:180 kgМасса:21 кгШирина:659 мм

Высота: 1662 мм

Показан пример без декоративных элементов, точность технического описания не гарантируется.

The shelving trolley is used for transporting, temporarily storing, preparing, and distributing GN containers.

Глубина:

Trolley with one compartment in robust, self-supporting and hygienic design, made of high-quality 1.0×1.0 " (25 \times 25 mm) stainless steel. 18 pairs of welded U-shaped shelf rails at distances of 3.0" (75 mm), with push-through and tilt protections on both sides as per DIN EN 18867-2. In addition to the vertical square tubes, two 0.8×0.4 " (20 \times 10 mm) rectangular-profile cross braces ensure user-friendly handling. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks, Ø 4.9" (125 mm), with pin fastening.

- Extensive equipment options allow for customised design and individual usage possibilities
- The design of the rails ensures safe insertion and removal of GN containers
- Swivel castors provide smooth driving and precise manoeuvring
- Locking devices guarantee secure driving and positioning
- High-quality workmanship with premium stainless steel enables easy cleaning and perfect hygiene
- Valuable materials ensure sustainability and value retention
- Robust construction guarantees high stability and load capacity

Дата обращения: 09.10.2025, 12:18:19 Значения величин и размеров являются приблизительными, точность технического описания не гарантируется. © Hupfer