

Push-through protection for shelves 900 mm

Технические характеристики изделия 0117422 | RG-RS/N5 600kg
1600/400

Технические характеристики



Размер ячейки:	150 mm
Max. section load	600
Carbon footprint (TM65 Basic Report)	37 kgCO ₂ e
Масса:	0.6 кг
Ширина:	899 мм
Глубина:	25 мм
Высота:	80 мм

*Показан пример без декоративных элементов,
точность технического описания не
гарантируется.*

Modular shelving system made of high-quality stainless steel 1.4301 in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.08" (50 × 2 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves.

Дата обращения: 21.05.2026,
08:49:29

*Значения величин и размеров являются приблизительными, точность
технического описания не гарантируется. © Hupfer*