

## Push-through protection for shelves 900 mm

Технические характеристики изделия 0117422 | RG-RS/N5 600kg  
1600/400

### Технические характеристики



<b>Размер ячейки:</b>	150 mm
<b>Max. section load</b>	600
<b>Carbon footprint (TM65 Basic Report)</b>	37 kgCO <sub>2</sub> e
<b>Масса:</b>	0.6 кг
<b>Ширина:</b>	899 мм
<b>Глубина:</b>	25 мм
<b>Высота:</b>	80 мм

*Показан пример без декоративных элементов,  
точность технического описания не  
гарантируется.*

Modular shelving system made of high-quality stainless steel 1.4301 in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.08" (50 × 2 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves.

Дата обращения: 23.04.2026,  
23:42:33

*Значения величин и размеров являются приблизительными, точность  
технического описания не гарантируется. © Hupfer*