

Gastronorm trolley for 40×GN 1/1

Технические характеристики изделия 0119012 | RWG 1/40 GN 75-B-L



Технические характеристики

| | |
|---------------------------|---------------------|
| Размер ячейки: | 75 mm |
| Тип шин: | Crosswise insertion |
| Полезная нагрузка: | 200 |
| Масса: | 25 кг |
| Ширина: | 659 мм |
| Глубина: | 739 мм |
| Высота: | 1818 мм |

Показан пример без декоративных элементов, точность технического описания не гарантируется.

The shelving trolley is used for transporting, temporarily storing, preparing, and distributing GN containers.

Trolley with one compartment in robust, self-supporting and hygienic design, made of high-quality 1.0 × 1.0" (25 × 25 mm) stainless steel. 20 pairs of welded L-shaped shelf rails at distances of 3.0" (75 mm), with push-through protections on both sides as per DIN EN 18867-2. In addition to the vertical square tubes, two 0.8 × 0.4" (20 × 10 mm) rectangular-profile cross braces ensure user-friendly handling. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks, ø 4.9" (125 mm), with pin fastening.

- Extensive equipment options allow for customised design and individual usage possibilities
- The design of the rails ensures safe insertion and removal of GN containers
- Swivel castors provide smooth driving and precise manoeuvring
- Locking devices guarantee secure driving and positioning
- High-quality workmanship with premium stainless steel enables easy cleaning and perfect hygiene
- Valuable materials ensure sustainability and value retention
- Robust construction guarantees high stability and load capacity

Дата обращения: 08.05.2026,
02:30:06

Значения величин и размеров являются приблизительными, точность технического описания не гарантируется. © Hupfer