



Показан пример без декоративных элементов, точность технического описания не гарантируется.

| Полезная нагрузка:  | 200 kg  |
|---------------------|---------|
| Мощность:           | 2000 W  |
| Входное напряжение: | 220 V   |
| Номинальный ток:    | 8,6 A   |
| Класс защиты:       | Class I |
| Частота:            | 50 Hz   |
| Macca:              | 69 кг   |
| Ширина:             | 992 мм  |
| Глубина:            | 760 мм  |
| Высота:             | 1082 мм |

Технические характеристики

Closed basket dispenser heated with circulating air, with height-adjustable platform for storing 25.6 × 20.9" (650 × 530 mm) baskets with small or difficult-to-stack crockery items.

Dispenser in self-supporting and hygienic design, made of high-quality stainless steel. Closed, smooth outer housing with thermal insulation through high-quality special insulation. Inner panelling on all sides, with high-quality mirror sheets for optimised energy usage. Open stacking compartment with removable basket that can be included in the stacking capacity, made of plastic-coated stainless steel as stacking platform with ball bearing platform guide. Consistent output height thanks to manually adjustable stainless steel tension spring system. Easy cleaning of stacking compartment from above and via a cleaning opening in the base plate. Reduced temperature losses and heating time thanks to cover hood made of grey polymer. Heated by power module with integrated motor, fan impeller and stainless steel tubular heating element for automatic convection air operation, operated using On/Off switch with integrated indicator light, thermostat-controlled using a continuously variable, ergonomically-shaped thermostat that is easy to read even from a distance, with temperature limiter as per VDE. Current supply via dimensionally stable and extractable spiral cable with angle plug. Dummy socket in switch plate as plug park. Four polymer corner bumpers, of which two at the upper corners of the structure that serve as bumpers and protect the equipment on all sides as well as building-side walls from being damaged, with integrated, ergonomically-shaped push bars. Dispenser runs on 4 swivel casters of which 2 with total locks, ø 4.9" (125 mm), fastened by means of screw-on plates and several screws.

The Hupfer basket dispenser KO/UH 65-53 has the lowest empty weight in comparison to other products, whileДата обращения: 20.07.2025,Значения величин и размеров являются приблизительными, точность05:39:49технического описания не гарантируется. © Hupfer

**Hupfer Metallwerke GmbH & Co. KG** Dieselstraße 20, 48653 Coesfeld · Postfach 1463, 48634 Coesfeld · Te*π*.: +49 2541 805-0 · Φaκc: +49 2541 805-111 · info@hupfer.de · www.hupfer.com info@hupfer.de · www.hupfer.com



## Basket dispenser fan-assisted heating 650×530 mm

two push handles installed on the corners of the unit ensure optimal handling properties. The ergonomically shaped push handles also guarantee effective protection against injuries to the hands. The installation height of 900 mm is the standard working height in food distribution. The guide basket, which comes as series standard, is the same as the non-rusting, stainless steel crockery baskets available as an optional accessory, and increases the stacking capacity by approx. 20 %.

Дата обращения: 20.07.2025, 05:39:49

Значения величин и размеров являются приблизительными, точность технического описания не гарантируется. © Hupfer

**Hupfer Metallwerke GmbH & Co. KG** Dieselstraße 20, 48653 Coesfeld · Postfach 1463, 48634 Coesfeld · Ten.: +49 2541 805-0 · Φaκc: +49 2541 805-111 · info@hupfer.de · www.hupfer.com info@hupfer.de · www.hupfer.com