Plate dispenser fan-assisted heating up to 80°C





Показан пример без декоративных элементов, точность технического описания не гарантируется.

Технические характеристики

Полезная нагрузка:	140 kg
Мощность:	1500 W
Входное напряжение:	220 V
Номинальный ток:	6,5 A
Класс защиты:	Class I
Частота:	50 Hz
Масса:	45 кг
Ширина:	930 мм
Глубина:	460 мм
Высота:	1072 мм

Plate dispenser for storing ø 7.5-10. 2" (190-260 mm) round plates in two stacking compartments heated with circulating air.

Dispenser in self-supporting and hygienic design, made of high-quality stainless steel. Closed, smooth outer housing with thermal insulation through high-quality special insulation. Inner panelling on all sides, with highquality mirror sheets for optimised energy usage. Open stacking compartments and stacking platforms in plastic-coated rod design. Three crockery guides per stacking compartment with plastic coating, variably adjustable without tools. Consistent output heights thanks to manually adjustable stainless steel tension spring systems. Easy cleaning of stacking compartments from above and via a cleaning opening in the base plate. Reduced temperature losses and heating time thanks to cover hoods made of polycarbonate with 3-point locking mechanism. Heated by power module with integrated motor, fan impeller and stainless steel tubular heating element for automatic convection air operation, operated using On/Off switch with integrated indicator light, thermostat-controlled using a continuously variable, ergonomically-shaped thermostat that is easy to read even from a distance, with temperature limiter as per VDE. Current supply via dimensionally stable and extractable spiral cable with angle plug. Dummy socket in switch plate as plug park. Four polymer corner bumpers, of which two at the upper corners of the structure that serve as bumpers and protect the equipment on all sides as well as building-side walls from being damaged, with integrated, ergonomically-shaped push bars. Dispenser runs on 4 swivel casters of which 2 with total locks, ø 4.9" (125 mm), fastened by means of screw-on plates and several screws.

Дата обращения: 21.07.2025, 04:30:15

Значения величин и размеров являются приблизительными, точность технического описания не гарантируется. © Hupfer

Hupfer Metallwerke GmbH & Co. KG Dieselstraße 20, 48653 Coesfeld · Postfach 1463, 48634 Coesfeld · Te*π*.: +49 2541 805-0 · Φaκc: +49 2541 805-111 · info@hupfer.de · www.hupfer.com info@hupfer.de · www.hupfer.com



Plate dispenser fan-assisted heating up to 80°C

The Hupfer plate dispenser TE/UH 2/19-26 VS not only provides shorter heating times, but also more uniform crockery temperatures. In addition, adapting the diameter of the stacking compartment for smaller crockery diameters reduces any loss of heat. The installation height of 900 mm is the standard working height in food serving practices.

Дата обращения: 21.07.2025, 04:30:15

Значения величин и размеров являются приблизительными, точность технического описания не гарантируется. © Hupfer

Hupfer Metallwerke GmbH & Co. KG Dieselstraße 20, 48653 Coesfeld · Postfach 1463, 48634 Coesfeld · Ten.: +49 2541 805-0 · Φaκc: +49 2541 805-111 · info@hupfer.de · www.hupfer.com info@hupfer.de · www.hupfer.com