

**Mobile bain-marie with tubular heating element****2×GN 1/1**

*Показан пример без декоративных элементов, точность технического описания не гарантируется.*

**Технические характеристики**

|                            |         |
|----------------------------|---------|
| <b>Полезная нагрузка:</b>  | 110     |
| <b>Мощность:</b>           | 1400 W  |
| <b>Входное напряжение:</b> | 220 V   |
| <b>Номинальный ток:</b>    | 6,0 A   |
| <b>Класс защиты:</b>       | Class I |
| <b>Частота:</b>            | 50 Hz   |
| <b>Масса:</b>              | 35 кг   |
| <b>Ширина:</b>             | 886 мм  |
| <b>Глубина:</b>            | 677 мм  |
| <b>Высота:</b>             | 900 мм  |

Heated mobile bain-marie for transporting and dispensing prepared food in GN containers, especially for mobile counters.

High-quality stainless steel trolley in stable, self-supporting and hygienic design. Enclosed design with seamlessly welded, fully insulated wells, can be heated wet or dry, with deep drawn level indicator for wet heating. Each well can hold a GN 1/1-200 or smaller container. The wells are specifically sloped at the bottom so that they can be completely drained via an externally adjustable 1/2" ball valve. Drain cock protected from accidental opening, each setting easily visible even at a distance. Heated by stainless steel tubular heating element, can be operated at the side via on/off switch with integrated indicator light and thermostatically controlled by variable, ergonomically designed temperature controller, also easily seen at a distance, with temperature limiter as per VDE. Power supplied by a sturdy retractable helix cable with angle plug and holder on the left narrow side. Firmly welded frame made of rectangular tube with welded-on shelf with all-round edged downfold, with board with circumferential profile edge all round the bottom of the trolley. Four solid polyethylene disc bumpers at the bottom for all-round protection of the device and walls from damage. There is an additional bumper with integrated finger grip above the controls. Trolley on 4 swivel castors, including 2 with total brakes,  $\varnothing$  125 mm, with pin fixing.

The Hupfer mobile bain marie SPA EB-2 LS is specially equipped with a recessed grip above the operating elements on the long side, and a power feed installed on the front side, for use at docking counters. The installation height of 900 mm is the standard working height in food distribution.

Дата обращения: 20.03.2026,  
08:37:52

*Значения величин и размеров являются приблизительными, точность  
технического описания не гарантируется. © Hupfer*