

## Mobile bain-marie with foil heating 3×GN 1/1

Технические характеристики изделия 0164207 | SPA ЗЕВ FH



*Показан пример без декоративных элементов, точность технического описания не гарантируется.*

### Технические характеристики

<b>Полезная нагрузка:</b>	165
<b>Мощность:</b>	2100 W
<b>Входное напряжение:</b>	230 V
<b>Номинальный ток:</b>	9,0 A
<b>Класс защиты:</b>	Class I
<b>Частота:</b>	50 Hz
<b>Масса:</b>	45 кг
<b>Ширина:</b>	1274 мм
<b>Глубина:</b>	677 мм
<b>Высота:</b>	900 мм

Foil-heated mobile bain-marie for transporting and dispensing prepared food in GN containers.

High-quality stainless steel trolley in stable, self-supporting and hygienic design. Enclosed design with seamlessly welded, fully insulated wells, can be heated wet, with deep drawn level indicator. Each well can hold a GN 1/1-200 or smaller container. The wells are specifically sloped at the bottom so that they can be completely drained via an externally adjustable 1/2" ball valve. Drain cock protected from accidental opening, each setting easily visible even at a distance. Heated by energy-efficient foil heaters with optimal heat conduction. Reduces heating time for water temperature of 90 °C to max. 30 minutes with radiant heat of approx. 35 °C on the outer housing. Heaters can be operated on the front via on/off switch with integrated indicator light and separately thermostatically controlled by variable, ergonomically designed temperature controller, also easily seen at a distance, with temperature limiter as per VDE. Power supplied by a sturdy retractable helix cable with angle plug and holder on the back. Firmly welded frame made of rectangular tube with welded-on shelf with all-round edged downfold, with board with circumferential profile edge all round the bottom of the trolley. Four solid polyethylene disc bumpers at the bottom and two polymer corner bumpers on the top of the body with integrated, ergonomically designed push handles, for all-round collision protection of the device and walls. Mobile trolley with 4 swivel castors, including 2 with total brakes, ø 125 mm, with pin fixing.

Дата обращения: 05.05.2026,  
16:14:11

*Значения величин и размеров являются приблизительными, точность технического описания не гарантируется. © Hupfer*