

## Технические характеристики



*Показан пример без декоративных элементов, точность технического описания не гарантируется.*

<b>Тип шин:</b>	Crosswise insertion
<b>Полезная нагрузка:</b>	320
<b>Мощность:</b>	600 W
<b>Холодопроизводительность:</b>	1039 W
<b>Входное напряжение:</b>	220 V
<b>Номинальный ток:</b>	16,0 A
<b>Класс защиты:</b>	Class I
<b>Частота:</b>	50 Hz
<b>Масса:</b>	230 кг
<b>Ширина:</b>	1114 мм
<b>Глубина:</b>	798 мм
<b>Высота:</b>	1973 мм

CoolMultiMobil for storing, transporting and cooling pre-portioned meal components on trays, grilles or in containers

Cooled interior with two front roller shutters that can be opened separately and inserts for keeping food that needs to be refrigerated cold in accordance with HACCP specifications. Powerful air curtain refrigeration for cooling even when the front roller shutters are open for serving food. Fan-assisted cooling for even and constant temperature distribution on all levels of the interior. Aluminium shutter on the front of each compartment with handle for one-handed use. Shutters can be opened separately on each compartment. Polymer rails ensure that shutters do not jam. Self-supporting torsionally rigid structure made of high quality stainless steel. Double-walled housing isolated on all sides with CFC-free, fire-retardant material. Housing with smooth stainless steel surfaces A vertical push bar made of round stainless steel tube on each corner of the housing. Simple and ergonomic manoeuvring of the transport trolley with two hands at any handle height. Housing protected from damage by polymer bumper strips round the entire chassis and top. Protruding edges and attachments on the housing also inside the area protected by the bumper strips. Additional bumper strip on the rear at 150 mm, level with common kitchen appliances. Front with built-in operating and control unit with digital temperature display, on/off switch and buttons for setting the temperature. Hygienic interior with smooth stainless steel surfaces. Air baffles in the rear and on the base can be removed for cleaning the interior.

Evaporator for refrigeration installed behind removable rear panel. Each compartment has two removable

Дата обращения: 02.04.2026,  
17:43:39

*Значения величин и размеров являются приблизительными, точность  
технического описания не гарантируется. © Hupfer*

## CoolMultiMobil

*Технические характеристики изделия 0164476-VK | СММ УК*

**HUPFER**  
we make work flow

stainless steel uprights with welded brackets for inserting trays, grilles or containers. Interior can be completely emptied in a few simple steps and can be cleaned very easily and hygienically. Optionally with two LED light strips for lighting the interior without glare. Power plug with sturdy cable gland and strain relief. Smooth power cable, approx. 1500 mm long. Stainless steel universal holder on the connection side for safely hanging the plug during transport. Technical compartment for refrigeration system below the cooling compartment. Inspection opening with triangular latch on the front for easy access to the refrigeration system.

Дата обращения: 02.04.2026,  
17:43:39

*Значения величин и размеров являются приблизительными, точность  
технического описания не гарантируется. © Hupfer*