

Känguruh push-in rack 3 StU

Технические характеристики изделия 7504595 | KÄ-EG 3StE
355/615/1041 L-Sch



Технические характеристики

Размер ячейки:	61.5 mm
Полезная нагрузка:	45
Масса:	16 кг
Ширина:	355 мм
Глубина:	615 мм
Высота:	1041 мм

*Показан пример без декоративных элементов,
точность технического описания не
гарантируется.*

Rack frame for storing sterilisation units.

Rack in robust, self-supporting, hygienic and sterilisable design, made of high-quality stainless steel square tubes with 15 pairs of shelf bolts each, at a modular dimension of 2.4" (61.5 mm) for height-adjustable L-shaped insert rails and one additional bolt each in between the third and fourth shelf bolt from top. It enables holding an additional disposal container measuring 23.6 × 11.8 × 7.9" (600 × 300 × 200 mm). Safe connection of rack and receiving system component (transport trolley, transfer dolly or base frame) by means of a locking wire that is released by lifting at the upper side of the rack. Once the rack has been retracted until it has reached the locking point and the wire is let loose, the wire latches safely and audibly into an anchor block. Two guide rails, made of stainless steel sheet and arranged centrally in longitudinal direction underneath the rack, provide additional safety along with matching guide rollers at the relevant system component. Mobile rack frame runs on 4 sterilisable fixed casters with \varnothing 3.0" (75 mm) caster body made of polymer.

Дата обращения: 07.04.2026,
17:46:03

*Значения величин и размеров являются приблизительными, точность
технического описания не гарантируется. © Hupfer*