

# Känguruh transport dolly 3 StU

Технические характеристики изделия 7504618 | KÄ-ÜW 3StE  
717/425/909 SH260

**HUPFER**  
we make work flow



## Технические характеристики

<b>Полезная нагрузка:</b>	60 kg
<b>Масса:</b>	19 кг
<b>Ширина:</b>	425 мм
<b>Глубина:</b>	909 мм
<b>Высота:</b>	766 мм

*Показан пример без декоративных элементов,  
точность технического описания не  
гарантируется.*

Transfer dolly as part of the KÄNGURUH-SYSTEM® for transferring a 3 STE rack frame and for transporting and storing sterile supplies containers or baskets.

Trolley in robust, self-supporting and hygienic design, made of high-quality stainless steel. Smooth platform in easy to clean, non-sterilisable design, hygienically-folded and rebated inwards burr-free, provided with reinforcement profiles on the underside. Coupling and fixing of rack frame with screwed, centrally arranged mushroom-head guide pins and an anchor block. Frontal coupling with two-point locking for safe docking to other system components such as transport trolleys and base frames. Onesided square tube push bar screwed to the platform, ergonomically angled. One manual release for the frontal coupling, underneath the push bar. One continuous polyethylene bumper strip at the front and two polyethylene bumper strips mounted on the sides at push bar level serve as bumpers and protect the trolley and other system components as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks,  $\varnothing$  4.9" (125 mm), fastened by means of screw-on plates and several screws.

Дата обращения: 09.10.2025,  
17:58:22

*Значения величин и размеров являются приблизительными, точность  
технического описания не гарантируется. © Hupfer*