

Känguruh push-in rack 6 StU

Технические характеристики изделия 7504622 | KÄ-EG 6StE
685/615/1041 L-Sch

Технические характеристики



Размер ячейки: 61.5 mm

TM65 Midlevel Report [Ссылка на сертификат](#)

Масса: 24 кг

Ширина: 685 мм

Глубина: 615 мм

Высота: 1041 мм

Показан пример без декоративных элементов,
точность технического описания не
гарантируется.

Rack frame for storing sterilisation units.

Rack with two compartments in robust, self-supporting, hygienic and sterilisable design, made of high-quality stainless steel square tubes with 15 pairs of shelf bolts each, at a modular dimension of 2.4" (61.5 mm) for height-adjustable L-shaped insert rails and one additional bolt each, located centrally in between the third and fourth shelf bolt from top. It enables holding an additional disposal container measuring 23.6 x 11.8 x 7.9" (600 x 300 x 200 mm). Safe connection of rack and receiving system component (transport trolley, transfer dolly or base frame) by means of a locking wire that is released by lifting at the upper side of the rack. Once the rack has been retracted until it has reached the locking point and the wire is let loose, the wire latches safely and audibly into an anchor block. Two guide rails, made of stainless steel sheet and arranged in longitudinal direction underneath the rack, provide additional safety along with matching guide rollers at the relevant system component. Mobile rack frame runs on 4 sterilisable fixed casters with ø 3.0" (75 mm) caster body made of polymer.