

Sterile goods transport cart for 6 StU

Технические характеристики изделия 7504647 | RTW/Z 10-6/1652

HUPFER
we make work flow



Технические характеристики

Полезная нагрузка:	200 kg
Масса:	91 кг
Ширина:	985 мм
Глубина:	751 мм
Высота:	1471 мм

*Показан пример без декоративных элементов,
точность технического описания не
гарантируется.*

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.12" (50 × 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded Ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 × 0.8 × 0.06" (50 × 20 × 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, Ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTW/Z 10-6/1652 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Дата обращения: 04.02.2026,
10:38:29

*Значения величин и размеров являются приблизительными, точность
технического описания не гарантируется. © Hupfer*