

Universal transport cart for 6 StU

HUPFER
we make work flow

Технические характеристики изделия 7504807 | ATW/VV 6StE
965/754/1487

Технические характеристики



Полезная нагрузка:	105 kg
Масса:	88 кг
Ширина:	965 мм
Глубина:	754 мм
Высота:	1487 мм

*Показан пример без декоративных элементов,
точность технического описания не
гарантируется.*

Transport trolley for universal use in clinic logistics cycles, for transport and storage of sterile and chemist's supplies, consumables and durables, laundry, food or for waste disposal. Single-walled trolley in robust, self-supporting design, made entirely of high-quality stainless steel in steam-diffusion tight, fully welded design. The interior and the outer housing are produced with a hermetically sealed finish, formed seamless, jointless and without undercut contours. The transport trolley is loaded on the long side via two double-walled, hinged doors that can be opened at an angle of approx. 270°. The automatically-latching doors are attached to robust stainless steel hinges mounted on vertical push bars; a 2-point door lock keeps the doors safely locked during transport. The left door is additionally fitted with a stop bead, so together with the trolley profiling and the door seals, optimum dust protection for the items to be transported is guaranteed. An extension also serves to keep the door open during loading, so no additional elements to be operated by a hand or foot are required. Interior with wire shelf that is tiltable and adjustable without tools; in horizontal position for placing e.g. sterile and chemist's supplies, in vertical position as front safeguard, e.g. for inserted laundry or waste bags. When using rack frames, the grating is stored in a vertical storage position at the rear wall and carried along undetachably. Four continuous vertical push bars (2 per side) for manoeuvring even with the doors open. Dimensionally stable chassis design, suitable for automatic trolley transport. Bumper protective feature provided by robust, continuous bumper strip made of impact-resistant plastic that is effective even with the doors open, with frontal recesses for connecting a towing device to the chassis. When fitted with non-corroding casters, the equipment is suitable for being cleaned in an automated washing device without restrictions. Matched to the washing device, a constant cleaning and drying result is achieved. Jets of water cannot ingress into the hollow spaces of the appliance; no water remains or is carried over following the drying process. Trolley runs on 2 swivel casters with

Дата обращения: 14.09.2025,
11:04:24

*Значения величин и размеров являются приблизительными, точность
технического описания не гарантируется. © Hupfer*

Universal transport cart for 6 StU

HUPFER
we make work flow

Технические характеристики изделия 7504807 | ATW/VV 6StE
965/754/1487

total lock, 2 fixed casters, fastened by means of screw-on plates and several screws.

Single-walled trolley in robust, self-supporting design, made entirely of high-quality stainless steel in steam-diffusion tight, fully welded design. The interior and the outer housing are produced with a hermetically sealed finish, formed seamless, jointless and without undercut contours. The transport trolley is loaded on the long side via two double-walled, hinged doors that can be opened at an angle of approx. 270°. The automatically-latching doors are attached to robust stainless steel hinges mounted on vertical push bars; a 2-point door lock keeps the doors safely locked during transport. The left door is additionally fitted with a stop bead, so together with the trolley profiling and the door seals, optimum dust protection for the items to be transported is guaranteed. An extension also serves to keep the door open during loading, so no additional elements to be operated by a hand or foot are required. Interior with wire shelf that is tiltable and adjustable without tools; in horizontal position for placing e.g. sterile and chemist's supplies, in vertical position as front safeguard, e.g. for inserted laundry or waste bags. When using rack frames, the grating is stored in a vertical storage position at the rear wall and carried along undetachably. Four continuous vertical push bars (2 per side) for manoeuvring even with the doors open. Dimensionally stable chassis design, suitable for automatic trolley transport. Bumper protective feature provided by robust, continuous bumper strip made of impact-resistant plastic that is effective even with the doors open, with frontal recesses for connecting a towing device to the chassis. When fitted with non-corroding casters, the equipment is suitable for being cleaned in an automated washing device without restrictions. Matched to the washing device, a constant cleaning and drying result is achieved. Jets of water cannot ingress into the hollow spaces of the appliance; no water remains or is carried over following the drying process. Trolley runs on 2 swivel casters with total lock, 2 fixed casters, fastened by means of screw-on plates and several screws.

Дата обращения: 14.09.2025,
11:04:24

*Значения величин и размеров являются приблизительными, точность
технического описания не гарантируется. © Hupfer*