

600 мм

## Stationary shelving set norm 12 with louvred shelf

## Показан пример без декоративных элементов, точность технического описания не гарантируется.

## Технические характеристики

Размер ячейки: 150 mm Max. section load 2000 **Carbon footprint (TM65 Basic Report)** 88 kgCO□e Macca: 32 кг Ширина: 1775 мм Глубина:

Высота: 2000 мм

Modular shelving system made of high-quality stainless steel in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for stand-alone placement, freely extendable lengthwise.

Uprights made of 1.  $2 \times 1$ . 2" (30  $\times$  30 mm) square tubes, connected by welded upright spokes made of 2.4  $\times$ 0.16" (60 × 4.0 mm) flat profiles that also serve as possibility for permanently attaching shelves. Additional attachment options through shelf lugs that are welded to the uprights in a 5.9" (150 mm) grid, enabling two included hook-on elements per upright to be attached variably. Upper covering caps made of plastic and heightadjustable aluminium screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright.

Дата обращения: 24.12.2025, 05:08:19

Значения величин и размеров являются приблизительными, точность технического описания не гарантируется. © Hupfer