

### Технические характеристики



*Показан пример без декоративных элементов, точность технического описания не гарантируется.*

<b>Размер ячейки:</b>	150 mm
<b>Max. bay load</b>	150
<b>Max. section load</b>	600
<b>Carbon footprint (TM65 Basic Report)</b>	1028 kgCO <sub>2</sub> e
<b>Масса:</b>	105 кг
<b>Ширина:</b>	4725 мм
<b>Глубина:</b>	600 мм
<b>Высота:</b>	1800 мм

Сплошная полка из алюминиевого листа толщиной 1,5 мм; по продольной стороне отогнутая и зафальцованная внутрь кромка высотой 40 мм, по фронтальной стороне отогнутая вниз кромка высотой 28 мм. В качестве дополнительной опоры для полок длиной 1200 – 1500 мм и глубиной 500 и 600 может использоваться U-образный профиль

- louvred shelf ensures ventilated, safe and hygienic storage and keeps the stored goods in peak condition
- high-quality stainless steel workmanship enables easy cleaning and perfect hygiene
- modular system allows for any design and extension and ensures the most efficient use of space
- valuable materials ensure sustainability and value retention
- robust construction guarantees high stability and high load-bearing capacity
- modular system ensures easy handling from assembly to cleaning with little effort